Produktdatenblatt



GF Malleable Fittings 240 - Muffe, reduziert, schwarz 2 - 1 1/2

1153705

- STA ... diese Fittings-Typen werden in Stahl gefertigt. Stahlteile bei Gewinde 1 mit 6-Kant statt Wulst.



Ausschreibungstexte GF Malleable Fittings 240 - Muffe, reduziert, schwarz

Spezifikation

- With their extensive history and tradition, malleable cast iron fittings are the most common pipe fittings. Because of their durability and mechanical strength, these fittings are very popular. The material is able to endure high mechanical stress and when combined with the standardized jointing method can be used in a wide range of applications.

Anwendung

- Sanitary, heating and gas installation, mechanical engineering (oil, cool pipework), construction of petrol stations (gas lines), sprinkler

GF Malleable Fittings 240 - Muffe, reduziert, schwarz 2 - 1 1/2

1153705



Product code

Item no EAN	7611205324711
Item no GF	770240138
Item no GTIN	07611205324711
Item no LVI	0755111
Item no NOBB	60639037
Item no NRF	1366769
Item no RSK	1313535
Item no VVS	004240167

Dimension

Höhe der Artikeleinheit	75
Länge der Artikeleinheit	75
Gewicht der Artikeleinheit	0,505
Breite der Artikeleinheit	65
Item_UOM	St.

Packaging

Verpackung GTIN PL1	07611205124717
Verpackung GTIN PL4	06414900122672
Verpackungshöhe PL1	200
Verpackungshöhe PL4	729
Verpackungslänge PL1	260
Verpackungslänge PL4	1200
Verpackungsmenge PL1	15
Verpackungsmenge PL4	810
Verpackungstyp PL1	Base_Box
Verpackungstyp PL4	Pallet

Verpackungsvolumen PL1	0,00988
Verpackungsband PL4	0,69984
Verpackungsgewicht PL1	7,789
Verpackungsgewicht PL4	429,05
Verpackungsbreite PL1	190
Verpackungsbreite PL4	800

Measurements

Z Measurement a	65
Z2	22

Technische Dokumente (wie Installationsanleitung etc.)

Dokumente herunterladen

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Georg Fischer Rohrleitungssysteme (Schweiz) AG

Amsler-Laffon-Strasse 9
8200, Schaffhausen
Schweiz

T +41 52 631 30 26
E ch.ps@georgfischer.com

+GF+