
Scheda tecnica



GF Malleable Fittings 340 - raccordo sede conica, zincato 1/8

1154393



Informazioni GF Malleable Fittings 340 - raccordo sede conica, zincato

Specifiche


- With their extensive history and tradition, malleable cast iron fittings are the most common pipe fittings. Because of their durability and mechanical strength, these fittings are very popular. The material is able to endure high mechanical stress and when combined with the standardized jointing method can be used in a wide range of applications.

Application

- Sanitary, heating and gas installation, mechanical engineering (oil, cool pipework), construction of petrol stations (gas lines), sprinkler

GF Malleable Fittings 340 - raccordo sede conica, zincato 1/8

1154393



Product code

Item no EAN	7611205438074
Item no GF	770340201
Item no GTIN	07611205438074
Item no RSK	1260872
Item no VVS	004340401

Dimensioni

Altezza unità articolo	26
Lunghezza unità articolo	29
Peso unitario dell'articolo	0,070
Larghezza unità articolo	38
Item_UOM	St.

Packaging

GTIN imballaggio PL1	07611205238070
GTIN imballaggio PL4	06414900240918
Altezza imballo PL1	100
Altezza imballo PL4	508
Lunghezza imballo PL1	260
Lunghezza imballo PL4	1200
Quantità imballo PL1	80
Quantità imballo PL4	5760
Tipo di imballaggio PL1	Base_Box
Tipo di imballaggio PL4	Pallet
Volume di imballaggio PL1	0,00494
Volume di imballaggio PL4	0,48768
Peso imballo PL1	5,736

Peso imballo PL4	424,352
Larghezza imballo PL1	190
Larghezza imballo PL4	800

Measurements

Spessore parete_s1	15
Spessore parete_s2	26
Spessore parete s3	15
Z Measurement a	38
Misura Z d	1/8
z1	24

Documenti tecnici

Download documenti

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Georg Fischer Rohrleitungssysteme (Schweiz) AG

Amsler-Laffon-Strasse 9
8200, Schaffhausen
Schweiz

T +41 52 631 30 26
E ch.ps@georgfischer.com

+GF+