Scheda tecnica



GF Malleable Fittings 374 - dado di raccordo, nero 1 S

1154590



Informazioni GF Malleable Fittings 374 - dado di raccordo, nero

Specifiche

- With their extensive history and tradition, malleable cast iron fittings are the most common pipe fittings. Because of their durability and mechanical strength, these fittings are very popular. The material is able to endure high mechanical stress and when combined with the standardized jointing method can be used in a wide range of applications.

Application

- Sanitary, heating and gas installation, mechanical engineering (oil, cool pipework), construction of petrol stations (gas lines), sprinkler

GF Malleable Fittings 374 - dado di raccordo, nero 1 S

1154590



Product code

Item no EAN	7611205344887
Item no GF	770374106
Item no GTIN	07611205344887
Item no NOBB	60639267
Item no NRF	1366999
Item no RSK	1261060
Item no VVS	004374108

Dimensioni

Altezza unità articolo	55
Lunghezza unità articolo	62
Peso unitario dell'articolo	0,141
Larghezza unità articolo	22
Item_UOM	St.

Packaging

GTIN imballaggio PL1	07611205144883
GTIN imballaggio PL4	06414900072540
Altezza imballo PL1	200
Altezza imballo PL4	729
Lunghezza imballo PL1	260
Lunghezza imballo PL4	1200
Quantità imballo PL1	90
Quantità imballo PL4	4860
Tipo di imballaggio PL1	Base_Box
Tipo di imballaggio PL4	Pallet
Volume di imballaggio PL1	0,00988

Volume di imballaggio PL4	0,69984
Peso imballo PL1	12,859
Peso imballo PL4	702,83
Larghezza imballo PL1	190
Larghezza imballo PL4	800

Measurements

Z Measurement a	22
Misura Z d	1
MISURA Z S	55

Documenti tecnici

Download documenti

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Georg Fischer Rohrleitungssysteme (Schweiz) AG

Amsler-Laffon-Strasse 9
8200, Schaffhausen
Schweiz

T +41 52 631 30 26
E ch.ps@georgfischer.com

+GF+